DVR-T4IP

speco technologies™

4 CH. Triplex Digital Video Recorder with 160GB HDD and Network Video Server

DVR-T4IP

Features

- 4 channels real-time video display and recording-120FPS
- Triplex Operation- simultaneous record, playback & network transfer
- Built in CD/RW copies files for archiving or emergency use
- USB port for JPEG data backup and software upgrade using USB flash drives
- Individual channel recording and playback settings-not global!
- High quality images with MPEG-2 video compression
- Network features include: remote searching and playback, remote live monitoring, remote configuration, remote camera control, remote upgrade and remote recording
- Network via LAN (DHCP), ADSL (dynamic & static IP address)
- Supports DDNS servers for easy use on dynamic networks
- 1 channel of audio recording
- Various recording triggers including motion detection, manual recording, external sensors and schedules
- IR remote control included

Also Available

DVR-T4IP/120 120 GB HDD

Package Includes:

DVR-T4IP	User manual
CD-ROM	Power Supply
Quick start guide	1 Year limited warranty

Specifications subject to change

For more information contact us at:
Speco Technologies 200 New Highway, Amityville, NY 11701 **Web: www.specotech.com**
Toll Free: 1-800-645-5516 **In Metro NY:** 631-957-8700 **Fax:** 631-957-9142 or 631-957-3880

DVR-T4IP

4 CH. Triplex Digital Video Recorder with 160GB HDD and Network Video Server

Specifications

Image System	NTSC, PAL selectable
Video Input	4 ch. BNC (NTSC/PAL)
Video Output	BNC connector x 2 (video out x1, VCR out x1) and 4 looping BNC outputs
Compression Method	MPEG-2
Recording Resolution: Quad Mode	NTSC: 720 X 480 (30FPS), PAL: 720x576 (25fps)
Recording Resolution: Mux Mode	NTSC: 720x480 (30fps), 360x240 (120fps), PAL: 720x576(25fps), 360x288 (100)fps
Record Quality	4 Levels (normal, enhanced, fine, super fine)
Live View/Recording Speed	Up to 120 FPS
Playback Type	Quad split or single camera
Playback Search	Date/time, event (alarm, motion detection)
Playback Speed	x1/4, x1/2, x1, x2, x4, x8, x16, x32, x64, x128, field by field (forward/backward)
Sensor Input	4 (NO/NC selectable)
Alarm Output	1 (NO/NC)
Aux Control In/Out	2/3 (Selectable function menu), alarm reset in, record start in, record on/off, alarm out, error out, record start out, disk full out, record status out
Audio	1CH, mono
Network	10 Base-T (STATIC, DHCP, PPPoE, E-mail & FTP) DDNS
Motion Detection	11x8, 8 Level security
Hard Disk	Internal
Backup Method	CD-RW, USB flash drive, network
Watermarking	Yes
PTZ Control	RS-485
System Log	Video loss, power on, power off, menu called, HDD full, FTP fail, email fail, etc.
Password Function	Power on/off, menu, record off, key lock
Digital Zoom	2 Times
Timer	Built-in real time clock
Power Source	Free voltage (100-240VAC, 50Hz/60Hz, 50W)
Dimensions	17"(W) x 15"(D) x 3.5"(H)
Operating Temperature	41˚F to 104˚F
Weight	12 lbs. (without HDD)

speco technologies™

For more information contact us at:
Speco Technologies 200 New Highway, Amityville, NY 11701 **Web: www.specotech.com**
Toll Free: 1-800-645-5516 **In Metro NY**: 631-957-8700 **Fax:** 631-957-9142 or 631-957-3880